

BÖHME EXTERIOR STAINS & FINISHES

BÖHME finishes represent the result of 40 years of research and work by Karoly Donders to develop quality low VOC wood finishes. He has developed hybrid natural-oil finishes that apply, penetrate and have the look of traditional oil coatings but clean up with soap and water. They are easy to maintain with simple re-coats and still <20g/L VOC. These remarkable Swiss finishes are now being manufactured in America through a partnership with Vermont Natural Coatings. We have tried and tested various coatings over the decades and have never found anything to equal Böhme. Whether for decking, siding, mill-work, doors or interior wood there is a Böhme solution.



Ligno

USE: Siding / Fencing

For all exterior wood applications except decks & stairs. Use on new or properly prepared finished wood.

- Ideal for use on exterior siding & fencing
- Excellent flow & uniform color
- Ready for second coat after 4-6 hours
- Soap & water cleanup

Lacking pigment **Clear* does not offer full UV protection & is not recommended as a standalone finish.



Terra Plus

USE: Decking / Fencing

Terra Plus Exterior deck stain is for use on decking & exterior stairs.

- For use on new or properly prepared decking
- Resistance to foot traffic
- Lasting protection against moisture, mold & mildew
- Ready for second coat after 12-24 hours
- Soap & water cleanup



Hydro-Oil Primer

USE: Presealer / Base Coat

Use on untreated or bare exterior wood to stabilize the wood structure. Ideal for cedar applications.

- Reduces the effect of water marks
- Provides a more even topcoat application
- Ready for second coat after 12-48 hours
- Should be used as a 1st coat for Ligno, Terra+ & Bomol
- Soap & water cleanup



Suncare 900

USE: Exterior Doors / Trim

For light colored wood (Pine, Douglas Fir, Hemlock, Spruce)

- Use on unfinished light wood
- Use as a prime coat for unfinished light wood
- Soap & water cleanup

EXTERIOR STAINS & FINISHES



Bomol

USE: Windows / Doors / Siding
For exterior wood trim, doors, windows, & siding. Use on new & prestained wood.

- Paint-like surface build with the penetration of a stain & good service life
- Ready for second coat after 24 hours
- Soap & water cleanup

Lacking pigment ***Clear** does not offer full UV protection & is not recommended as a standalone finish.

Aging Stain

USE: Siding / Decks / Fencing
For use on new wood

- Provides a natural looking aged gray finish
- Evens out differences in natural wood tones
- Ready for second coat after 6-8 hours
- Does not require topcoat
- Soap & water cleanup

INTERIOR STAINS & FINISHES



Left side was treated with Suncare 800 UV while right side was left to darken.

Suncare 800 UV

USE: Interior Paneling / Trim
For light colored woods (Pine, Douglas Fir, Hemlock, Spruce) to maintain the original light color.

- Reduces the yellowing and darkening of light wood caused by UV irradiation without changing the natural appearance of the wood
- 1st or base coat under final finish
- Dries in 4 to 6 hours
- Soap & water cleanup



Jet Finish

USE: Interior Paneling / Trim
For use on new wood

- Interior clear matte finish with excellent chemical & mechanical resistance.
- Fast drying 2 to 3 hours. Available in clear & white tone.
- Soap & Water cleanup.